



**11926-2 ORFS MALE O-RING /
SAE O-RING BOSS S-SERIES ISO 11926-2**

PART NO.	THREAD		O-RING		DIMENSIONS				
	E	F	E	F	A	B	L	S1	
1F0-04	9/16" × 18	7/16" × 20	O011	O904	9.8	11	28.7	17	
1F0-04-05	9/16" × 18	1/2" × 20	O011	O905	9.8	11	28.7	17	
1F0-04-06	9/16" × 18	9/16" × 18	O011	O906	9.8	12	29.5	17	
1F0-04-08	9/16" × 18	3/4" × 16	O011	O908	9.8	14	33.5	22	
1F0-06-04	11/16" × 16	7/16" × 20	O012	O904	11.2	11	31	19	
1F0-06-05	11/16" × 16	1/2" × 20	O012	O905	11.2	11	30.9	19	
1F0-06	11/16" × 16	9/16" × 18	O012	O906	11.2	12	31.9	19	
1F0-06-08	11/16" × 16	3/4" × 16	O012	O908	11.2	14	35	22	
1F0-06-10	11/16" × 16	7/8" × 14	O012	O910	11.2	16	38.5	27	
1F0-08-06	13/16" × 16	9/16" × 18	O014	O906	12.8	12	34.5	22	
1F0-08	13/16" × 16	3/4" × 16	O014	O908	12.8	14	36.6	22	
1F0-08-10	13/16" × 16	7/8" × 14	O014	O910	12.8	16	40.5	27	
1F0-08-12	13/16" × 16	1.1/16" × 12	O014	O912	12.8	18.5	44.5	32	
1F0-10	1" × 14	7/8" × 14	O016	O910	15.5	16	43.1	27	
1F0-10-08	1" × 14	3/4" × 16	O016	O908	15.5	14	41	27	
1F0-10-12	1" × 14	1.1/16" × 12	O016	O912	15.5	18.5	47	32	
1F0-12-10	1.3/16" × 12	7/8" × 14	O018	O910	17	16	46	32	
1F0-12	1.3/16" × 12	1.1/16" × 12	O018	O912	17	18.5	48.6	32	
1F0-12-16	1.3/16" × 12	1.5/16" × 12	O018	O916	17	18.5	49.8	38	
1F0-16-12	1.7/16" × 12	1.1/16" × 12	O021	O912	17.5	18.5	50	38	
1F0-16	1.7/16" × 12	1.5/16" × 12	O021	O916	17.5	18.5	50.3	38	
1F0-16-20	1.7/16" × 12	1.5/8" × 12	O021	O920	17.5	18.5	52	50	
1F0-20-16	1.11/16" × 12	1.5/16" × 12	O025	O916	17.5	18.5	52	46	
1F0-20	1.11/16" × 12	1.5/8" × 12	O025	O920	17.5	18.5	52.3	50	
1F0-24-20	2" × 12	1.5/8" × 12	O029	O920	17.5	18.5	54	55	
1F0-24	2" × 12	1.7/8" × 12	O029	O924	17.5	18.5	54.1	55	

Note: F end is connected with ISO 11926-1 port.