



ORFS MALE O-RING / METIRC MALE S-SERIES ISO6149-2

PART NO.	THREAD		O-RING		DIMENSIONS			
	E	F	E	F	A	B	L	S1
1FH-04-10	9/16" × 18	M10 × 1	O011	O08.1 × 1.6	9.8	9.5	28	17
1FH-04-12	9/16" × 18	M12 × 1.5	O011	O09.3 × 2.4	9.8	11	29.5	17
1FH-06-12	11/16" × 16	M12 × 1.5	O012	O09.3 × 2.4	11.2	11	31	19
1FH-06-14	11/16" × 16	M14 × 1.5	O012	O11.3 × 2.4	11.2	11	31	19
1FH-06-16	11/16" × 16	M16 × 1.5	O012	O13.3 × 2.4	11.2	12.5	33.5	22
1FH-08-16	13/16" × 16	M16 × 1.5	O014	O13.3 × 2.4	12.8	12.5	36	22
1FH-08-18	13/16" × 16	M18 × 1.5	O014	O15.3 × 2.4	12.8	14	36.5	24
1FH-08-22	13/16" × 16	M22 × 1.5	O014	O19.3 × 2.4	12.8	15	37.5	27
1FH-10-22	1" × 14	M22 × 1.5	O016	O19.3 × 2.4	15.5	15	40.5	27
1FH-12-22	1.3/16" × 12	M22 × 1.5	O018	O19.3 × 2.4	17	15	45.5	32
1FH-12-27	1.3/16" × 12	M27 × 2	O018	O23.5 × 3.0	17	18.5	44	32
1FH-16-33	1.7/16" × 12	M33 × 2	O021	O29.5 × 3.0	17.5	18.5	51	41
1FH-20-42	1.11/16" × 12	M42 × 2	O025	O38.5 × 3.0	17.5	19	54.5	50
1FH-24-48	2" × 12	M48 × 2	O029	O44.5 × 3.0	17.5	21.5	57	55

Note: F end is fit for ISO 6149-1 port.