



**TN**

**TS**

Filettatura:  
UNF/UN

Thread:  
UNF/UN

**TN/TS 92 UNF/UN**

– Raccordo di estremità dirritto filettatura UNF/UN

– Male Stud couplings UNF/UN

Serie Series	Ø Tubo Tube O.D. d <sub>1</sub>	PN	Ø F	Ø N	I	L1	L	CH2	CH1	L2	O-Ring* (Shore A Ca 90)	Completo Complete		Peso - Weight kg.×100 P.		
												Articolo Item	Codice Code	Completo Complete	Solo corpo Only body	
L	8	315	7/16-20 UNF	14,4	9	10	25	17	17	17	8,92 ×1,83	<b>TN 92- 8L 7/16-20UNF</b>	<b>TN092L08U07</b>	3,6	2,0	
	10		7/16-20 UNF	14,4	9	11	26	17	19	19,5	8,92 ×1,83	<b>TN 92-10L 7/16-20UNF</b>	<b>TN092L10U07</b>	5,4	3,3	
	12		9/16-18 UNF	17,6	10	11	26	19	22	19,5	11,9 ×1,98	<b>TN 92-12L 9/16-18UNF</b>	<b>TN092L12U09</b>	6,0	3,2	
	12		3/4-16 UNF	22,3	11	13	28	24	22	19,5	16,36×2,20	<b>TN 92-12L 3/4-16UNF</b>	<b>TN092L12U12</b>	7,7	4,9	
	12		7/8-14 UNF	25,5	12,7	12,5	29	27	22	19,5	19,18×2,46	<b>TN 92-12L 7/8-14UNF</b>	<b>TN092L12U14</b>	9,6	6,9	
	15		3/4-16 UNF	22,3	11	14	29	24	27	22	16,36×2,20	<b>TN 92-15L 3/4-16UNF</b>	<b>TN092L15U12</b>	12,3	7,8	
	18		3/4-16 UNF	22,3	11	14,5	31	27	32	22	16,36×2,20	<b>TN 92-18L 3/4-16UNF</b>	<b>TN092L18U12</b>	13,5	6,7	
	18		7/8-14 UNF	25,5	12,7	14,8	31	27	32	22	19,18×2,46	<b>TN 92-18L 7/8-14UNF</b>	<b>TN092L18U14</b>	14,0	7,1	
	22	160	7/8-14 UNF	25,5	12,7	16,8	33	32	36	24	19,18×2,46	<b>TN 92-22L 7/8-14UNF</b>	<b>TN092L22U14</b>	17,9	9,0	
	22		1"1/16-12 UN	31,9	15	16,5	33	32	36	24	23,47×2,95	<b>TN 92-22L 1"1/16-12UN</b>	<b>TN092L22U17</b>	19,1	10,2	
	22		1"5/16-12 UN	38,2	15	17,5	34	41	36	24	29,74×2,95	<b>TN 92-22L 1"5/16-12UN</b>	<b>TN092L22U21</b>	26,1	17,4	
	28		1"1/16-12 UN	31,9	15	17,5	34	41	41	25	23,47×2,95	<b>TN 92-28L 1"1/16-12UN</b>	<b>TN092L28U17</b>	25,1	15,0	
	28		1"5/16-12 UN	38,2	15	17,5	34	41	41	25	29,74×2,95	<b>TN 92-28L 1"5/16-12UN</b>	<b>TN092L28U21</b>	25,9	15,7	
	35		1"5/16-12 UN	38,2	15	17,5	39	46	50	28	29,74×2,95	<b>TN 92-35L 1"5/16-12UN</b>	<b>TN092L35U21</b>	36,2	21,0	
35	1"5/8-12 UN		47,7	15	17,5	39	50	50	28	37,46×3	<b>TN 92-35L 1"5/8 - 12UN</b>	<b>TN092L35U26</b>	40,2	25,0		
42	1"5/8-12 UN		47,7	15	19	42	55	60	30	37,46×3	<b>TN 92-42L 1"5/8 - 12UN</b>	<b>TN092L42U26</b>	53,7	30,3		
S	8		630	7/16-20 UNF	16	9	15	30	17	19	22	8,92×1,83	<b>TN 92- 8S 7/16-20UNF</b>	<b>TN092S08U07</b>	5,4	3,2
	10			9/16-18 UNF	17,6	10	14,5	31	19	22	23	11,9 ×1,98	<b>TN 92-10S 9/16-18UNF</b>	<b>TN092S10U09</b>	7,8	4,5
	12	9/16-18 UNF		17,6	10	14,5	31	22	24	25	11,9 ×1,98	<b>TN 92-12S 9/16-18UNF</b>	<b>TN092S12U09</b>	9,7	6,0	
	12	3/4-16 UNF		22,3	11	17,5	34	24	24	25	16,36×2,20	<b>TN 92-12S 3/4-16UNF</b>	<b>TN092S12U12</b>	10,9	7,3	
	16	400	3/4-16 UNF	22,3	11	15,5	34	24	30	27	16,36×2,20	<b>TN 92-16S 3/4-16UNF</b>	<b>TN092S16U12</b>	15,0	8,0	
	16		7/8-14 UNF	25,5	12,7	18,8	37	27	30	27	19,18×2,46	<b>TN 92-16S 7/8-14UNF</b>	<b>TN092S16U14</b>	16,4	9,3	
	20		3/4-16 UNF	22,3	11	20,5	42	32	36	31	16,36×2,20	<b>TN 92-20S 3/4-16UNF</b>	<b>TN092S20U12</b>	24,6	13,4	
	20		7/8-14 UNF	25,5	12,7	20,8	42	32	36	31	19,18×2,46	<b>TN 92-20S 7/8-14UNF</b>	<b>TN092S20U14</b>	25,0	13,7	
	20		1"1/16-12 UN	31,9	15	20,5	42	32	36	31	23,47×2,95	<b>TN 92-20S 1"1/16-12UN</b>	<b>TN092S20U17</b>	25,9	14,8	
	25		1"1/16-12 UN	31,9	15	23	47	36	46	35	23,47×2,95	<b>TN 92-25S 1"1/16-12UN</b>	<b>TN092S25U17</b>	42,0	20,5	
	25		1"5/16-12 UN	38,2	15	23	47	41	46	35	29,74×2,95	<b>TN 92-25S 1"5/16-12UN</b>	<b>TN092S25U21</b>	46,8	25,7	
	30		1"5/16-12 UN	38,2	15	23,5	50	46	50	38	29,74×2,95	<b>TN 92-30S 1"5/16-12UN</b>	<b>TN092S30U21</b>	56,8	32,8	
	30		1"5/8-12 UN	47,7	15	23,5	50	50	50	38	37,46×3	<b>TN 92-30S 1"5/8 - 12UN</b>	<b>TN092S30U26</b>	63,2	39,7	
	38		315	1"5/8-12 UN	47,7	15	26	57	55	60	42	37,46×3	<b>TN 92-38S 1"5/8 - 12UN</b>	<b>TN092S38U26</b>	86,3	52,2

- Le dimensioni di ingombro si intendono a raccordo chiuso.

- Overall sizes are with closed fitting.

- Per ordinare i raccordi in ACCIAIO INOX (AISI 316) sostituire nel codice di ordinazione la lettera "T" con la lettera "I"

- To order stainless steel fittings (AISI 316), replace the letter "T" with the letter "I"

- Gamma di temperature senza riduzioni di pressione con i raccordi in acciaio con guarnizioni gomma in NBR (di serie) e FPM (su richiesta): NBR (Perbunan): da -35 a +100°C - FPM (Viton): da -25 a +120°C (Per i raccordi in acciaio inox AISI 316 vedere pagine tecniche)

- Temperature range without pressure reductions with steel connections fitted with seals in NBR (standard) and FPM (to order): NBR (Perbunan): from -35 to +100°C - FPM (Viton): from -25 to +120°C (For stainless steel fittings (AISI 316) see technical pages)

- Per ordinare il "solo corpo" sostituire la lettera "N" con la lettera "S"

- To order only body replace the letter "N" with the letter "S"